FLOS

RAY FI

Environment

Finish

Mounting Floor

I x MAX 105W E27 HSGS or I LED 8W E27 740lm 2700K dimmer Lamps description

Indoor

Technical description

White, Glass, Black

Floor lamp providing diffused lighting. Steel tube (10 mm diam.) structure, welded, brushed and chrome-plated. Diffuser

support disk in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored,

blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the

regulation of light brightness.

ELECTRICAL

Without **Emergency**

On the cable there is the electronic dimmer which allows the Switching

regulation of light brightness with a dial.

Voltage (V) 220/240

PHYSICAL

Diameter (mm) 360

Power cord Supply

2300 Cord length (mm)

Construction material Aluminum, Glass, Steel

Weight (kg) 5.0 (met) - 8.0 (glass)






Ray FI designed by Rodolfo Dordoni

Floor lamp providing diffused lighting.

F5916030 Black

F5916009 White F5915020 Glass

DIMENSIONS



CERTIFICATIONS









IP 20

www.flos.com info@flos.it



Ray FI . Lamps





HSGS 105W E27

LED 8W E27 740lm 2700K

designed by Rodolfo Dordoni

Lamp wattage:

Lamp wattage:

Floor lamp providing diffused lighting.

105 W

8 W

F5916030

Ray FI

Black

Lamp category:

Lamp category: **LED**

F5916009

White Glass

Halogen mains

Socket:

F5915020

Socket: E27


E27

Lamp type: **HSGS**

Lamp type:

LED

DIMENSIONS



CERTIFICATIONS









FLOS

RAY F2

Finish

Mounting Floor

Lamps description I x MAX 205W E27 HSGS or I LED 21W E27 2452lm 3000K dimmer

Environment Indoor

White, Glass, Black

Technical description Floor lamp providing diff

Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in diecast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Latheshaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the

regulation of light brightness.




Ray F2 designed by Rodolfo Dordoni

Floor lamp providing diffused lighting.

F5921030 Black F5921009 White F5920020 Glass

DIMENSIONS



ELECTRICAL

Emergency Without

Switching On the cable there is the electronic dimmer which allows the

regulation of light brightness with a dial.

Voltage (V) 220/240

PHYSICAL

Diameter (mm) 430

Supply Power cord

Cord length (mm) 1900

Construction material Aluminum, Glass, Steel

Weight (kg) 6.2 (met) - 9.2 (glass)



CERTIFICATIONS
















Ray F2 . Lamps





HSGS 205W E27

Lamp wattage:

205 W

Lamp category:

Halogen mains

Socket:

E27

Lamp type:

HSGS

LED 21W E27 2452lm

Lamp wattage:

21 W

Lamp category:

LED

Socket:

E27

Lamp type:

LED




Ray F2 designed by Rodolfo Dordoni

Floor lamp providing diffused lighting.

F5921030 Black F5921009 White F5920020 Glass

DIMENSIONS



CERTIFICATIONS











